# Local Roots CDL Drivers

### Commercial Driver's License - Overview

- CDL Fact Sheet
- Vehicle Pre-Trip Inspection
  - External
  - o In-Cab
  - Trailer
  - Air Brakes
  - Skills Test
  - Maneuvering
  - On-Road Driving
  - Automatic Failure

#### WHO MUST HAVE A COMMERCIAL DRIVER'S LICENSE (CDL)?

Anyone who drives a commercial motor vehicle. The definition of a commercial motor vehicle is:

- a) a combination of vehicles with a gross vehicle weight rating of 26,001 or more pounds, provided the vehicle being towed is in excess of 10,000 pounds;
- b) a single vehicle with a gross vehicle weight rating of 26,001 or more pounds;
- c) a vehicle designed to transport 16 or more passengers, including the driver;
- d) a school bus; or
- e) any vehicle that is transporting hazardous materials and is required to be placarded in accordance with State and Federal regulations.

#### LRL Vehicle GVWR:

- F-350 10,400 (#0006)
- NPR 14,500 (#0010)
- F-550 19,500 (#0002)
- F-600 22,000 (#0015)
- o F-650 25,999 (#0007)
- o F-750 25,999 (#0005)
- o F-750 33,000 (#0011)

#### LRL Trailer GVWR:

- Bri-Mar Dump 5,000 (#4139)
- Finn BB 6,000 (#5767)
- Cargo 10,000 (#0311)
- Currahee Equip 14,000 (#4781)
- Sure-Trac Dump 14,000 (#7548)
- Sure-Trac Equip 25,900 (#1988)

WHO MUST HAVE A COMMERCIAL DRIVER'S LICENSE (CDL)?

Commercial motor vehicles do not include:

- a) implements of husbandry;
- b) any motor home or recreational trailer operated solely for personal use; or
- c) motorized construction equipment, including, but not limited to, motorscrapers, backhoes, motorgraders, compactors, excavators, tractors, trenchers and bulldozers.

#### WHO MUST SUBMIT A SELF-CERTIFICATION FORM?

Every driver who currently has a commercial driver's license, as well as every driver applying for a commercial learner's permit, must self-certify the type of driving in which they operate or expect to operate in i.e., Non-excepted Interstate; Non-excepted Intrastate; Excepted Interstate; or Excepted Intrastate. The self-certification process will identify commercial drivers that operate in Non-excepted transportation, therefore identifying which drivers are required to submit a copy of their valid Medical Examiner's Certificate to PennDOT.

#### WHAT ARE THE CLASSES OF COMMERCIAL DRIVER LICENSES?

CLASS A - combination vehicle with a gross vehicle weight rating of 26,001 pounds or more, provided the gross vehicle weight rating of the vehicle being towed is in excess of 10,000 pounds.

CLASS B - single vehicles with a gross vehicle weight rating of 26,001 pounds or more, or any such vehicle towing a vehicle not in excess of 10,000 pounds.

CLASS C - single vehicles with a gross vehicle weight rating of less than 26,001 pounds if the vehicle is: transporting hazardous materials requiring placarding; is designed to transport 16 or more passengers, including the driver; or, is a school bus.

#### WHAT ARE THE REQUIRED ENDORSEMENTS?

The operation of certain vehicles also require the drivers to possess commercial endorsements in addition to possessing the proper class of license.

- endorsement H authorizes the driver to operate a vehicle transporting hazardous materials requiring placarding
- endorsement N authorizes the driver to operate tank vehicles
- endorsement X hazardous materials and tank vehicle (H,N)
- endorsement P authorizes the driver to operate vehicles carrying passengers
- endorsement S authorizes the driver to operate a school bus (a School Bus endorsement card will be issued annually)
- endorsement T authorizes the driving of double and triple trailers
- restriction L restricts the driver to vehicles NOT equipped with air brakes
- restriction M restricts the driver from a class A bus
- restriction N restricts the driver from a class A or B bus
- restriction E restricts the driver from driving manual transmission commercial vehicles
- restriction K limits a driver to only operate in intrastate commerce
- restriction O restricts a driver from driving a truck tractor/semi-trailer combination
- restriction Z restricts a driver from driving a full air-brake equipped vehicle

#### WHAT TESTS DO I NEED TO TAKE?

You will need to pass the Knowledge Tests that are required for the class of license, restriction, and endorsements you wish to possess. A general knowledge test for the Class A or Class B and C license must be successfully completed by all CDL applicants. The information needed to pass these tests is contained in the CDL driver's manual.

#### Class A CDL Test Requirements

- License Knowledge Test (written) 70 Questions
- L/Z Air Brake Restriction Removal (written) 25 Questions
- Skills Test Includes Pre-Trip Inspection, Vehicle Parking Exercise, Off-the-Road Maneuver, On-Road Driving

#### **Internal Inspection & External Inspection**

During the Vehicle inspection, you must show that the vehicle is safe to drive. You will have to walk around the vehicle and point to or touch each item and explain to the examiner what you are checking and why. You will NOT have to crawl under the hood or under the vehicle.

You should be able to identify each part of the vehicle and tell the examiner what you are looking for or inspecting.

Repetition is key!

#### CDL Vehicle Inspection Memory Aid

#### **Combination Vehicles** Front of Vehicle, Lights/Reflectors, Engine Compartment & Steering Components Steering Axie: Suspension • Brakes • Tires Driver Door Fuel Area Under Vehicle . Drive Shaft Exhaust Frame Drive Axie(s) Suspension Brakes · Tires Coupling Devices - Truck Trailer Rear of Truck/Tractor & Lights/Reflectors Trailer Components Front, Side, Lights & Reflectors • Frame . Landing Gear Tandem Release Trailer Axle(s) Suspension • Brakes • Tires

Rear of Trailer & Lights/Reflectors

#### Straight Truck or Bus

Front of Vehicle, Lights/Reflectors, Engine Compartment & Steering Components

> Passenger Door Fuel Area

#### Steering Axie: Suspension

- Brakes
   Tiror
- Tires

#### Driver Door Fuel Area (Truck)

#### Under Vehicle

- Drive ShaftExhaust
- Frame

#### Drive Axie(s)

- SuspensionBrakes
- Tires



Rear of Bus/Truck & Lights/Reflectors

### **Pre-Trip Inspection Terminology & Tips**

- PMS Properly Mounted, Secure
  - If it's mounted (almosted everything is)
- CBB Cracked, Bent, Broken
  - Metal, plastic or other hard surfaces
- ABC Abrasions, Bulges, Cuts
  - Rubber (hoses, tires, belts..)
- "Not leaking" If it has fluid/air going through it or in it. (at both ends)

### **Engine Compartment (Engine Off)**

- Leaks/Hoses
  - Look for puddles on the ground.
  - Look for dripping fluids on underside of engine and transmission.
  - Inspect hoses for condition and leaks.
- Oil Level
  - Indicate where dipstick is located.
  - See that oil level is within safe operating range. Level must be above refill mark.

### **Engine Compartment (Engine Off)**

- Coolant Level
  - Inspect reservoir sight glass, or
  - (If engine is not hot), remove radiator cap and check for visible coolant level.
- Power Steering Fluid
  - Indicate where power steering fluid dipstick is located.
  - Check for adequate power steering fluid level.
  - Level must be above refill mark.

### **Engine Compartment (Engine Off)**

- Engine Compartment Belts
- Check the following belts for snugness (up to 3/4 inch play at center of belt), cracks, or frays:
  - Power steering belt.
  - Water pump belt.
  - Alternator belt.
  - Air compressor belt.

Note: If any of the components listed above are not belt driven, you must: Tell the examiner which component(s) are not belt driven.

Make sure component(s) are operating properly, are not damaged or leaking, and are mounted securely.

### **Entering the Vehicle**

When entering and exiting the vehicle - be sure to maintain 3-points of contact.

Always face the vehicle when entering and exiting the vehicle.

### Starting the Vehicle

Depress clutch. Place gearshift lever in neutral (or park, for automatic transmissions). Start engine, then release clutch slowly.

- Oil Pressure Gauge
  - Make sure oil pressure gauge is working.
  - Check that pressure gauge shows increasing or normal oil pressure or that the warning light goes off.
  - If equipped, oil temperature gauge should begin a gradual rise to the normal operating range.

- Temperature Gauge
  - Make sure the temperature gauge is working.
  - Temperature should begin to climb to the normal operating range or temperature light should be off.
- Air Gauge
  - Make sure the air gauge is working properly.
  - Build air pressure to governor cut-out, roughly 120- 140 psi.
- Ammeter/Voltmeter
  - Check that gauges show alternator and/or generator is charging or that warning light is off.

### **Cab Check/Engine Start (Internal)**

- Mirrors and Windshield
  - Mirrors should be clean and adjusted properly from the inside.
  - Windshield should be clean with no illegal stickers, no obstructions, or damage to the glass.
- Emergency Equipment
  - Check for spare electrical fuses.
  - Check for three red reflective triangles, 6 fusees or 3 liquid burning flares.
  - Check for a properly mounted, charged and rated fire extinguisher.

Note: If the vehicle is not equipped with electrical fuses, you must mention this to the examiner.

- Wipers/Washers
  - Check that wiper arms and blades are secure, not damaged, and operate smoothly.
  - If equipped, windshield washers must operate correctly.
- Horn
  - Check that air horn and/or electric horn work.
- Heater/Defroster
  - Test that the heater and defroster work.

### **Cab Check/Engine Start (Internal)**

- Lights/Reflectors/Reflector Tape Condition (Sides & Rear)
- Test that dash indicators work when corresponding lights are turned on:
  - Left turn signal. Right turn signal.
  - Four-way emergency flashers.
  - High beam headlight.
  - Anti-lock Braking System (ABS) indicator.

Note: Checks of brake, turn signal and four-way flasher functions must be done separately.

#### **Cab Check/Engine Start (Internal)**

- Lights/Reflectors/Reflector Tape Condition (Sides & Rear)
- Check that all external lights and reflective equipment are clean and functional. Light and reflector checks include:
  - Clearance lights (red on rear, amber elsewhere).
  - Headlights (high and low beams).
  - Taillights.
  - Backing lights.
  - Turn signals.
  - Four-way flashers.
  - o Brake lights.
  - Red reflectors (on rear) and amber reflectors (elsewhere).
  - Reflector tape condition

Note: Checks of brake, turn signal and four-way flasher functions must be done separately.

- Parking Brake Check
  - With the parking brake engaged (trailer brakes released on combination vehicles),
     check that the parking brake will hold vehicle by gently trying to pull forward with parking brake on.
  - With the parking brake released and the trailer parking brake engaged (combination vehicles only), check that the trailer parking brake will hold vehicle by gently trying to pull forward with the trailer parking brake on.

### **Cab Check/Engine Start (Internal)**

Air Brake Check (Air Brake Equipped Vehicles Only)

Failure to perform all three components of the air brake check correctly will result in an automatic failure of the vehicle inspection test. Air brake safety devices vary. However, this procedure is designed to see that any safety device operates correctly as air pressure drops from normal to a low air condition. For safety purposes, in areas where an incline is present, you will use wheel chocks during the air brake check. The proper procedures for inspecting the air brake system are as follows:

- Air Brake Check Applied Pressure Test
  - 1. With the air pressure built up to governor cutoff (120 140 psi), shut off the engine, chock your wheels if necessary, release the parking brake (all vehicles), and the tractor protection valve (combination vehicle) and fully apply the foot brake. Hold the foot brake for one minute. Check the air gauge to see if the air pressure drops more than three pounds in one minute (single vehicle) or four pounds in one minute (combination vehicle).

- Air Brake Check Warning Light and Buzzer Test
  - 2. Without re-starting the engine, turn electrical power to the "on" or "battery charge" position. Begin fanning off the air pressure by rapidly applying and releasing the foot brake. Low air warning devices (buzzer, light, flag) should activate before air pressure drops below 60 psi or level specified by the manufacturer..

- Air Brake Check Tractor/Trailer Protection Valve Pop Out Test
  - 3. Continue to fan off the air pressure. At approximately 40 psi on a tractor-trailer combination vehicle (or level specified by the manufacturer), the tractor protection valve and parking brake valve should close (pop out). On other combination vehicle types and single vehicle types, the parking brake valve should close (pop out).

- Service Brake Check
  - You will be required to check the application of air or hydraulic service brakes. This procedure is designed to determine that the brakes are working correctly and that the vehicle does not pull to one side or the other. Pull forward at 5 mph, apply the service brake and stop. Check to see that the vehicle does not pull to either side and that it stops when brake is applied.
- Safety Belt
  - Check that the safety belt is securely mounted, adjusts, latches properly and is not ripped or frayed.

### **External Inspection - Steering**

- Steering Box/Hoses
  - Check that the steering box is securely mounted and not leaking. Look for any missing nuts, bolts, and cotter keys.
  - Check for power steering fluid leaks or damage to power steering hoses.
- Steering Linkage
  - See that connecting links, arms, and rods from the steering box to the wheel are not worn or cracked.
  - Check that joints and sockets are not worn or loose and that there are no missing nuts, bolts, or cotter keys.

### **External Inspection - Steering**

- Suspension Springs/Air/Torque
  - Look for missing, shifted, cracked, or broken leaf springs.
  - Look for broken or distorted coil springs.
  - If vehicle is equipped with torsion bars, torque arms, or other types of suspension components, check that they are not damaged and are mounted securely.
  - Air ride suspension should be checked for damage and leaks.

#### **External Inspection - Steering**

- Mounts
  - Look for cracked or broken spring hangers, missing or damaged bushings, and broken, loose, or missing bolts, u-bolts or other axle mounting parts.
  - (The mounts should be checked at each point where they are secured to the vehicle frame and axle[s]).
- Shock Absorbers
  - $\circ$  See that shock absorbers are secure and that there are no leaks.

Note: Be prepared to perform the same suspension components inspection on every axle (power unit and trailer, if equipped).

#### **External Inspection - Brakes**

- Slack Adjusters and Pushrods
  - Look for broken, loose, or missing parts.
  - For manual slack adjusters, the brake pushrod should not move more than one inch
    (with the brakes released) when pulled by hand.
- Brake Chambers
  - See that brake chambers are not leaking, cracked, or dented and are mounted securely.
- Brake Hoses/Lines
  - Look for cracked, worn, or leaking hoses, lines, and couplings.

### **External Inspection - Brakes**

- Drum Brake
  - Check for cracks, dents, or holes. Also check for loose or missing bolts.
  - Check for contaminants such debris or oil/grease.
  - Brake linings (where visible) should not be worn dangerously thin.
- Brake Linings
  - On some brake drums, there are openings where the brake linings can be seen from outside the drum. For this type of drum, check that a visible amount of brake lining is showing.

Note: Be prepared to perform the same brake components inspection on every axle (power unit and trailer, if equipped).

### **External Inspection - Wheels**

- Rims
  - Check for damaged or bent rims.
  - Rims cannot have welding repairs.
- Hub Oil Seals/Axle Seals
  - See that hub oil/grease seals and axle seals are not leaking and, if wheel has a sight glass, oil level is adequate.
- Lug Nuts
  - Check that all lug nuts are present, free of cracks and distortions, and show no signs of looseness such as rust trails or shiny threads.
  - Make sure all bolt holes are not cracked or distorted.

### **External Inspection - Wheels**

- Tires
- The following items must be inspected on every tire:
  - Tread depth: Check for minimum tread depth (4/32 on steering axle tires, 2/32 on all other tires).
  - Tire condition: Check that the tread is evenly worn and look for cuts or other damage to tread or sidewalls. Also, make sure that valve caps and stems are not missing, broken, or damaged.
  - Tire inflation: Check for proper inflation by using a tire gauge. Note: You will not get credit if you simply kick the tires to check for proper inflation.

### **External Inspection - Wheels**

- Spacers or Budd Spacing
  - o If equipped, check that spacers are not bent, damaged, or rusted through. Spacers should be evenly centered, with the dual wheels and tires evenly separated.

Note: Be prepared to perform the same wheel inspection on every axle (power unit and trailer, if equipped).

### **External Inspection - Side of Vehicle**

- Door(s)/Mirror(s)
  - Check that door(s) are not damaged and that they open and close properly from the outside. Hinges should be secure with seals intact.
  - Check that mirror(s) and mirror brackets are not damaged and are mounted securely with no loose fittings.
- Fuel Tank
  - Check that tank(s) are secure, cap(s) are tight, and that there are no leaks from tank(s)
    or lines.

## **External Inspection - Side of Vehicle**

- Drive Shaft
  - See that drive shaft is not bent or cracked.
  - Couplings should be secure and free of foreign objects.
- Exhaust System
  - Check system for damage and signs of leaks such as rust or carbon soot.
  - System should be connected tightly and mounted securely.
- Frame
  - Look for cracks, broken welds, holes or other damage to the longitudinal frame members, cross members, box, and floor.

### **External Inspection - Rear of Vehicle**

- Splash Guards
  - If equipped, check that splash guards or mud flaps are not damaged and are mounted securely.
- Doors/Ties/Lifts
  - Check that doors and hinges are not damaged and that they open, close, and latch properly from the outside, if equipped.
  - Ties, straps, chains, and binders must also be secure.
  - If equipped with a cargo lift, look for leaking, damaged or missing parts and explain how it should be checked for correct operation.
  - Lift must be fully retracted and latched securely.

- Air/Electric Lines
  - Listen for air leaks. Check that air hoses and electrical lines are not cut, chafed, spliced, or worn (steel braid should not show through).
  - Make sure air and electrical lines are not tangled, pinched, or dragging against tractor parts.
- Catwalk/Steps
  - Check that the catwalk is solid, clear of objects, and securely bolted to tractor frame.
  - Check that steps leading to the cab entry and catwalk (if equipped) are solid, clear of objects, and securely bolted to tractor frame.

- Mounting Bolts
  - Look for loose or missing mounting brackets, clamps, bolts, or nuts. Both the fifth wheel and the slide mounting must be solidly attached.
  - On other types of coupling systems (i.e., ball hitch, pintle hook, etc.), inspect all coupling components and mounting brackets for missing or broken parts.
- Hitch Release Lever
  - Check to see that the hitch release lever is in place and is secure.

- Locking Jaws
  - $\circ$  Look into fifth wheel gap and check that locking jaws are fully closed around the kingpin.
  - On other types of coupling systems (i.e., ball hitch, pintle hook, etc.), inspect the locking mechanism for missing or broken parts and make sure it is locked securely. If present, safety cables or chains must be secure and free of kinks and excessive slack.
- 5th Wheel Skid Plate
  - Check for proper lubrication and that 5th wheel skid plate is securely mounted to the platform and that all bolts and pins are secure and not missing.

- Platform (Fifth Wheel)
  - Check for cracks or breaks in the platform structure which supports the fifth wheel skid plate.
  - Release Arm (Fifth Wheel) If equipped, make sure the release arm is in the engaged position and the safety latch is in place.
  - Kingpin/Apron/Gap Check that the kingpin is not bent. Make sure the visible part of the apron is not bent, cracked, or broken. Check that the trailer is lying flat on the fifth wheel skid plate (no gap).

- Locking Pins (Fifth Wheel)
  - If equipped, look for loose or missing pins in the slide mechanism of the sliding fifth wheel. If air powered, check for leaks.
  - Make sure locking pins are fully engaged.
  - Check that the fifth wheel is positioned properly so that the tractor frame will clear the landing gear during turns.
- Sliding Pintle
  - Check that the sliding pintle is secured with no loose or missing nuts or bolts and cotter pin is in place.

- Tongue or Draw-bar
  - Check that the tongue/draw-bar is not bent or twisted and checks for broken welds and stress cracks.
  - Check that the tongue/draw-bar is not worn excessively.
- Tongue Storage Area
  - Check that the storage area is solid and secured to the tongue.
  - Check that cargo in the storage area i.e. chains, binders, etc. are secure.

## **External Inspection - Trailer**

- Air/Electrical Connections
  - Check that trailer air connectors are sealed and in good condition.
  - Make sure glad hands are locked in place, free of damage or air leaks.
  - Make sure the trailer electrical plug is firmly seated and locked in place.
- Header Board
  - If equipped, check the header board to see that it is secure, free of damage, and strong enough to contain cargo.
  - If equipped, the canvas or tarp carrier must be mounted and fastened securely.
  - On enclosed trailers, check the front area for signs of damage such as cracks, bulges, or holes.

### **External Inspection - Side of Trailer**

- Landing Gear
  - Check that the landing gear is fully raised, has no missing parts, crank handle is secure, and the support frame is not damaged.
  - If power operated, check for air or hydraulic leaks.
- Frame
  - Look for cracks, broken welds, holes or other damage to the frame, cross members, box, and floor.

### **External Inspection - Side of Trailer**

- Doors/Ties/Lifts
  - If equipped, check that doors are not damaged.
  - Check that doors open, close, and latch properly from the outside.
  - Check that ties, straps, chains, and binders are secure.
  - If equipped with a cargo lift, look for leaking, damaged or missing parts and explain how it should be checked for correct operation.
  - Lift should be fully retracted and latched securely.

## **External Inspection - Remainder of Trailer**

- Follow same inspection procedures as power unit regarding the following components:
  - Wheels
  - Suspension system
  - Brakes
  - Doors/ties/lift
  - Splash guards

### **Taking the CDL Inspection Test**

• If you are applying for a Class A CDL, you will be required to perform one of the four versions of a Vehicle inspection in the vehicle you have brought with you for testing. Each of the four tests are equivalent and you will not know which test you will take until just before the testing begins. All of the tests include an engine start, an in-cab inspection, and an inspection of the coupling system. Then, your test may require an inspection of the entire vehicle or only a portion of the vehicle which your CDL Examiner will explain to you.

- Your basic control skills could be tested using one or more of the following exercises off-road or somewhere on the street during the road test:
  - Straight line backing.
  - Offset back/right
  - Offset back/left
  - Parallel park (driver side).
  - Parallel park (conventional).
  - Alley dock.

## Scoring


- Encroachments The examiner will score the number of times you touch or cross over an exercise boundary line or cone with any portion of your vehicle. Each encroachment will count as an error.
- Pull-ups When a driver stops and pulls forward to clear an encroachment or to get a better position, it is scored as a "pull-up". Stopping without changing direction does not count as a pull-up. You will not be penalized for initial pull-ups. However, an excessive number of pull-ups, will count as errors.

## Scoring (Continued)


- Outside Vehicle Observations (Looks) You may be permitted to safely stop and exit the vehicle to check the external position of the vehicle (look). When doing so, you must place the vehicle in neutral and set the parking brake(s). Then, when exiting the vehicle, you must do so safely by facing the vehicle and maintaining three points of contact with the vehicle at all times (when exiting a bus, maintain a firm grasp on the handrail at all times). If you do not safely secure the vehicle or safely exit the vehicle it may result in an automatic failure of the basic control skills test.
- The maximum number of times that you may look to check the position of your vehicle is two (2) except for the Straight Line Backing exercise, which allows one look. Each time you open the door, move from a seated position where in physical control of the vehicle or on a bus walk to the back of a bus to get a better view, it is scored as a "look".

- Scoring (Continued)
  - Final Position/Inside Parallel It is important that you finish each exercise exactly as the
    examiner has instructed you. If you do not maneuver the vehicle into its final position as
    described by the examiner, you will be penalized and could fail the basic skills test.


- Exercises
  - Straight Line Backing
    - You may be asked to back your vehicle in a straight line between two rows of cones without touching or crossing over the exercise boundaries.




- Exercises
  - Offset Back/Right
    - You may be asked to back into a space that is to the right rear of your vehicle. You will drive straight forward the outer boundary. From that position you must back the vehicle into the opposite lane until the front of your vehicle has passed the first set of cones without striking boundary lines or cones.




- Exercises (Continued)
  - Offset Back/Left
    - You may be asked to back into a space that is to the left rear of your vehicle. You will drive straight forward the outer boundary. From that position, you must back the vehicle into the opposite lane until the front of your vehicle has passed the first set of cones without striking boundary lines or cones.



- Exercises (Continued)
  - Parallel Park (Driver Side)
    - You may be asked to park in a parallel parking space that is on your left. You are to drive past the entrance to the parallel parking space with your vehicle parallel to the parking area; and back into the space without crossing front, side or rear boundaries marked by cones. You are required to get your entire vehicle completely into the space.




- Exercises (Continued)
  - Parallel Park (Conventional)
    - You may be asked to park in a parallel parking space that is on your right. You are to drive past the entrance to the parallel parking space with your vehicle parallel to the parking area; and back into the space without crossing front, side or rear boundaries marked by cones. You are required to get your entire vehicle completely into the space.



Exercises (Continued)

## Alley Dock

You may be asked to sight-side back your vehicle into an alley. You will drive past the alley and position your vehicle parallel to the outer boundary. From that position, back into the alley bringing the rear of your vehicle within three feet of the rear of the alley without touching boundary lines or cones. Your vehicle must be straight within the alley/lane when you have completed the maneuver.



- How You Will Be Tested
  - You will drive over a test route that has a variety of traffic situations. At all times during the test, you must drive in a safe and responsible manner; and you must:
  - Wear your safety belt.
  - Obey all traffic signs, signals, and laws.
  - Complete the test without an accident or moving violation.
  - During the driving test, the examiner will be scoring you on specific driving maneuvers as well as on your general driving behavior. You will follow the directions of the examiner. Directions will be given to you so you will have plenty of time to do what the examiner has asked. You will not be asked to drive in an unsafe manner.
  - If your test route does not have certain traffic situations, you may be asked to simulate a traffic situation. You will do this by telling the examiner what you are or would be doing if you were in that traffic situation.

- The following list of actions and/or behaviors will constitute an automatic failure of the "Onroad Driving" portion of the test.
  - Accident: an accident, however slight, which the applicant could have prevented.
  - Seat belt: failure to use seatbelt.
  - Striking or jumping curb: driving one or more wheels over the curb or onto the sidewalk;
     making contact with the curb, sidewalk or marker.
  - Failure to verbalize and demonstrate all three parts of the air brake check correctly
  - Headlights: failure to use headlights when required.
  - Stop sign offenses: failure to stop for stop sign; failure to stop before proceeding into intersection; failure to make second stop if necessary.

- Red light offenses: failure to stop for a red light; failure to decelerate when approaching a yellow light; entering into the intersection as light turns red.
- Failure to stop at railroad crossing: crossing railroad tracks before stopping when required to stop.
- Failure to yield right of way: failure to yield to pedestrian; failure to yield to on-coming driver when making left turn; failure to yield promptly to emergency vehicles; failure to yield to traffic having right of way.
- Driving in opposite lane continuously: crossing double yellow line and remaining in opposite lane for extended period of time.
- Improper passing: insufficient clearance for pass; passing within or two close to intersection; returning to lane too quickly after passing; forcing overtaken vehicle to slow down; passing on right where illegal; passing in no-passing zone.

- Speeding: exceeding the posted speed limit by 5 mph or more for an extended period of time without the driver reducing speed to within the posted limit.
- Improper stopping: failure to stop before clearly marked stop line or crosswalk; stopping unnecessarily on roadway.
- Failure to obey traffic laws
- Encroachment: Encroachment of clearly marked stop line.
- Lack of Cooperation: refusal to obey instructions of examiner, refusal to attempt maneuver when instructed by examiner.
- Offering bribes or gratuity to examiner.
- Vehicle control: vehicle out of gear more than length of vehicle; vehicle stops in traffic to regain gear; stalls engine on road.

- Speed control according to conditions: driving too fast for conditions; sliding or skidding due to speed; failure to decelerate when appropriate.
- Signal usage: failure to signal before starting, stopping, turning or changing lanes.
- Shifting while crossing railroad tracks.

- Turns
  - You have been asked to make a turn:
    - Check traffic in all directions.
    - Use turn signals and safely get into the lane needed for the turn.
  - As you approach the turn:
    - Use turn signals to warn others of your turn.
    - Slow down smoothly, change gears as needed to keep power, but do not coast unsafely. Unsafe coasting occurs when your vehicle is out of gear (clutch depressed or gearshift in neutral) for more than the length of your vehicle.

- Turns (Continued)
  - o If you must stop before making the turn:
    - Come to a smooth stop without skidding.
    - Come to a complete stop behind the stop line, crosswalk, or stop sign.
  - If stopping behind another vehicle, stop where you can see the rear tires on the vehicle ahead of you (safe gap).
  - Do not let your vehicle roll.
  - Keep the front wheels aimed straight ahead.

- Turns (Continued)
  - When ready to turn:
    - Check traffic in all directions.
    - Keep both hands on the steering wheel during the turn.
    - Keep checking your mirror to make sure the vehicle does not hit anything on the inside of the turn.
  - Vehicle should not move into oncoming traffic.
  - Vehicle should finish turn in correct lane.

- Turns (Continued)
  - After turn:
    - Make sure turn signal is off.
    - Get up to speed of traffic, use turn signal, and move into right-most lane when safe to do so (if not already there).
    - Check mirrors and traffic.

- Intersections
  - As you approach an intersection:
    - Check traffic thoroughly in all directions.
    - Decelerate gently.
    - Brake smoothly and, if necessary, change gears.
    - If necessary, come to a complete stop (no coasting) behind any stop signs, signals, sidewalks, or stop lines maintaining a safe gap behind any vehicle in front of you.
    - Your vehicle must not roll forward or backward.

- Intersections (Continued)
  - When driving through an intersection:
    - Check traffic thoroughly in all directions.
    - Decelerate and yield to any pedestrians and traffic in the intersection.
    - Do not change lanes while proceeding through the intersection.
    - Keep your hands on the wheel.
  - Once through the intersection:
    - Continue checking mirrors and traffic.
    - Accelerate smoothly and change gears as necessary.

- Urban Business
  - During this part of the test, you are expected to make regular traffic checks and maintain a safe following distance. Your vehicle should be centered in the proper lane (right-most lane) and you should keep up with the flow of traffic but not exceed the posted speed limit.
- Lane Changes
  - During multiple lane portions of the test, you will be asked to change lanes to the left, and then back to the right. You should make the necessary traffic checks first, then use proper signals and smoothly change lanes when it is safe to do so.

- Expressway or Rural/Limited Access Highway
  - Before entering the expressway:
    - Check traffic.
    - Use proper signals.
    - Merge smoothly into the proper lane of traffic.
  - Once on the expressway:
    - Maintain proper lane positioning, vehicle spacing, and vehicle speed.
    - Continue to check traffic thoroughly in all directions.
  - When exiting the expressway:
    - Make necessary traffic checks.
    - Use proper signals.
    - Decelerate smoothly in the exit lane.
    - Once on the exit ramp, you must continue to decelerate within the lane markings and maintain adequate spacing between your vehicle and other vehicles.

- Stop/Start
  - For this maneuver, you will be asked to pull your vehicle over to the side of the road and stop as if you were going to get out and check something on your vehicle. You must check traffic thoroughly in all directions and move to the right-most lane or shoulder of road.
  - As you prepare for the stop:
    - Check traffic. Activate your right turn signal.
    - Decelerate smoothly, brake evenly, change gears as necessary.
    - Bring your vehicle to a full stop without coasting.

- Stop/Start (Continued)
  - Once stopped:
    - Vehicle must be parallel to the curb or shoulder of the road and safely out of the traffic flow.
    - Vehicle should not be blocking driveways, fire hydrants, intersections, signs, etc.
    - Cancel your turn signal.
    - Activate your four-way emergency flashers.
    - Apply the parking brake.
    - Move the gear shift to neutral or park.
    - Remove your feet from the brake and clutch pedals.

- Stop/Start (Continued)
  - When instructed to resume:
    - Check traffic and your mirrors thoroughly in all directions.
    - Turn off your four-way flashers.
    - Activate the left turn signal.
    - When traffic permits, you should release the parking brake and pull straight ahead.
    - Do not turn the wheel before your vehicle moves.
    - Check traffic from all directions, especially to the left.
    - Steer and accelerate smoothly into the proper lane when safe to do so.
    - Once your vehicle is back into the flow of traffic, cancel your left turn signal.

- Curve
  - When approaching a curve:
    - Check traffic thoroughly in all directions.
    - Before entering the curve, reduce speed so further braking or shifting is not required in the curve.
    - Keep vehicle in the lane.
    - Continue checking traffic in all directions.

- Railroad Crossing
  - Before reaching the crossing, all commercial drivers should:
    - Decelerate, brake smoothly, and shift gears as necessary. Look and listen for the presence of trains. Check traffic in all directions. Do not stop, change gears, pass another vehicle, or change lanes while any part of your vehicle is in the crossing.
  - If you are driving a bus, a school bus, or a vehicle displaying placards, you should be prepared to observe the following procedures at every railroad crossing (unless the crossing is exempt):
    - As the vehicle approaches a railroad crossing, activate the four-way flashers.

- Railroad Crossing (Continued)
  - Stop the vehicle within 50 feet but not less than 15 feet from the nearest rail.
  - Listen and look in both directions along the track for an approaching train and for signals indicating the approach of a train.
  - If operating a bus, you may also be required to open the window and door prior to crossing tracks.
  - Keep hands on the steering wheel as the vehicle crosses the tracks.
  - Do not stop, change gears, or change lanes while any part of your vehicle is proceeding across the tracks.
  - Four-way flashers should be deactivated after the vehicle crosses the tracks.
  - Continue to check mirrors and traffic.

- Railroad Crossing (Continued)
  - Not all driving road test routes will have a railroad crossing. You may be asked to explain and demonstrate the proper railroad crossing procedures to the examiner at a simulated location.

- Bridge/Overpass/Sign
  - After driving under an overpass, you may be asked to tell the examiner what the posted clearance or height was. After going over a bridge, you may be asked to tell the examiner what the posted weight limit was. If your test route does not have a bridge or overpass, you may be asked about another traffic sign. When asked, be prepared to identify and explain to the examiner any traffic sign which may appear on the route.

- General Driving Behaviors
  - You will be scored on your overall performance in the following general driving behavior categories:
    - Clutch Usage (Manual Transmission)
    - Gear Usage (Manual Transmission)
    - Brake Usage
    - Lane Usage
    - Steering
    - Regular Traffic Checks
    - Use of Turn Signals

- General Driving Behaviors
  - Clutch Usage (Manual Transmission)
    - Always use clutch to shift.
    - You must double-clutch when shifting.
    - Do not rev or lug the engine.
    - Do not ride clutch to control speed, coast with the clutch depressed, or "pop" the clutch.
  - Gear Usage (Manual Transmission)
    - Do not grind or clash gears.
    - Select gear that does not rev or lug engine.
    - Do not shift in turns and intersections.

- General Driving Behaviors
  - Brake Usage
    - Do not ride or pump brake.
    - Do not brake harshly.
    - Brake smoothly using steady pressure.

- General Driving Behaviors
  - Lane Usage
    - Do not put vehicle over curbs, sidewalks, or lane markings.
    - Stop behind stop lines, crosswalks, or stop signs.
    - Complete a turn in the proper lane on a multiple lane road (vehicle should finish a left turn in the lane directly to the right of the centerline).
    - Finish a right turn in the right-most (curb) lane.
    - Move to or remain in right-most lane unless lane is blocked.

- General Driving Behaviors
  - Steering
    - Do not over or under steer the vehicle.
    - Keep both hands on the steering wheel at all times unless shifting.
    - Once you have completed shift, return both hands to the steering wheel.

- General Driving Behaviors
  - Regular Traffic Checks
    - Check traffic regularly.
    - Check mirrors regularly.
    - Check mirrors and traffic before, while in and after an intersection.
    - Scan and check traffic in high volume areas and areas where pedestrians are expected to be present.

- General Driving Behaviors
  - Use of Turn Signals
    - Use turn signals properly.
    - Activate turn signals when required.
    - Activate turn signals at appropriate times.
    - Cancel turn signals upon completion of a turn or lane change.